

# FBR-POWER-WINCHLINE® ROPE I / II

## 高性能尼龙单丝复合缆绳I型/尼龙单丝复合缆绳II型

密度:1.14g/cm³	Specific Gravity :1.14g/cm³ Immersed
熔点:215°C	Melting Point :215°C
伸长率:23%	Elongation : 23%
耐磨性:很好	Abrasion Resistance : Excellent
抗紫外线:好	UV Resistance :Good
抗化学腐蚀:好	Chemical Resistance :Good

### 高性能尼龙单丝复合缆绳 I 型:

FBR-POWER-WINCHLINE® ROPE I 缆绳, 习惯称为“牛筋绳”, 选用优质进口尼龙单丝, 运用世界领先的工艺技术生产, 比国内同类产品更轻, 更强, 更久, 伸长更大, 维护简单、操作方便, 真正达到世界一流质量的产品。其中, 牛筋绳12股结构比6股结构性能更加稳定。

### 尼龙单丝复合缆绳 II 型:

FBR-POWER-WINCHLINE® ROPE II 缆绳, 习惯称为“牛筋绳”, 选用优质国产尼龙单丝, 运用世界领先的工艺技术生产, 比国内同类产品更耐用, 操作方便, 真正达到世界一流质量的产品。其中, 牛筋绳12股结构比6股结构性能更加稳定。

应用领域: 船用系泊, 自动缆车。

### FBR-POWER-WINCHLINE® ROPE I:

It is similar to "Atlas" rope, which is made of high quality imported nylon monofilament. With the world's leading technology, the rope is lighter, stronger, longer service life, greater elongation than the same category of domestic product. It is truly a product with world-class quality.

### FBR-POWER-WINCHLINE® ROPE II:

It is similar to "Atlas" rope, which is made of high quality nylon monofilament. With the world's leading technology, the rope is lighter, stronger, longer service life, greater elongation than the same category of domestic product. It is truly a product with world-class quality.

**Application:** Ship mooring, automatic cable car.



# I 6-STRAND AND 12-STRAND

## I型 六股、十二股参数表

尺寸 Size		重量 Weight		I型断裂强力	
直径 mm Dia.	圆周 Inch Cir.	米重 g/m	kg/220m	千牛 kN	吨 ton
40	5	1040	229	304	31.0
44	5-1/2	1250	275	412	42.0
48	6	1480	326	490	50.0
52	6-1/2	1640	361	531	54.2
56	7	2000	440	651	66.4
60	7-1/2	2160	475	686	70.0
62	7-3/4	2350	517	784	80.0
64	8	2450	539	795	81.1
68	8-1/2	2810	619	925	94.4
70	8-3/4	3110	684	1010	103.0
72	9	3250	715	1040	106.1
78	9-3/4	3770	829	1180	120.4
84	10-1/2	4270	939	1380	141.0
90	11-1/4	5040	1109	1620	165.3
96	12	5860	1289	1870	191.0

●如果需要其它尺寸,可以根据客户要求定制。 ● Other sizes are available upon request.

# II 6-STRAND AND 12-STRAND

## II型 六股、十二股参数表

尺寸 Size		重量 Weight		II型断裂强力	
直径 mm Dia.	圆周 Inch Cir.	米重 g/m	kg/220m	千牛 kN	吨 ton
40	5	1030	227	275	28.1
44	5-1/2	1250	275	333	34.0
48	6	1470	324	392	40.0
52	6-1/2	1720	379	454	46.3
56	7	2020	444	520	53.0
60	7-1/2	2320	510	606	61.0
62	7-3/4	2470	543	637	65.0
64	8	2630	579	669	68.0
68	8-1/2	2990	658	753	76.8
70	8-3/4	3160	695	794	81.0
72	9	3340	735	836	85.3
78	9-3/4	3940	867	986	100.6
84	10-1/2	4570	1005	1140	116.3
90	11-1/4	5240	1153	1310	133.6
96	12	5950	1310	1460	149.0

●如果需要其它尺寸,可以根据客户要求定制。 ● Other sizes are available upon request.