



Streamer Hydrophones



High quality streamer hydrophones available as 1, 8, 12 or 20 element MF designs and 24 element LF design. Each is supplied with a pre-amplifier and connectors for standard seismic acquisition systems.

Key Features

- Filled with silicon oil for neutral buoyancy
- Supplied with robust 50m tow leader
- Complete with pre-amplifier
- Standard models and customised units with grouped elements available
- Medium frequency and low frequency versions

Technical Specification

Streamer hydrophone, fluid filled with multi-elements

Model number	AH1	AH360/8
Tow leader	50m	50m
Array Tube type	Polyurethane	Polyurethane
Array tube length	4.5m	4.5m
Number of elements	1	8
Element spacing	n/a	360mm
Array sensitivity	-187dB ref 1V per μ Pa	-169dB ref 1V per μ Pa
Fluid type	Polydimethylsiloxane, PMX561	Polydimethylsiloxane, PMX561
Power	Battery, 9V alkaline, PP3/MN1604	Battery, 9V alkaline, PP3/MN1604
Frequency response	140Hz to 10kHz (-3dB)	140Hz to 10kHz (-3dB)
Signal output	Up to 8V peak to peak	Up to 8V peak to peak
Preamp	Single ended, fixed gain	Single ended, fixed gain
Connector type	BNC, 50/75 ohm cable can be used	BNC, 50/75 ohm cable can be used
Elements		
Dimensions	55 x 16 x 10 mm	55 x 16 x 10 mm
Sensitivity	-187dB ref 1V per μ Pa	-187dB ref 1V per μ Pa
Depth recoverable	30m max	30m max
Operating depth	Typical 10m	Typical 10m
Type	Non acceleration cancelling	Non acceleration cancelling
Resonance	@ 9 kHz	@ 9 kHz



Streamer Hydrophones

Model number	AH250/12	AH150/20
Tow leader	50m	50m
Array Tube type	Polyurethane	Polyurethane
Array tube length	4.5m	4.5m
Number of elements	12	20
Element spacing	250mm	150mm
Array sensitivity	-165dB ref 1V per μ Pa	-161dB ref 1V per μ Pa
Fluid type	Polydimethylsiloxane, PMX561	Polydimethylsiloxane, PMX561
Power	Battery, 9V alkaline, PP3/MN1604	Battery, 9V alkaline, PP3/MN1604
Frequency response	140Hz to 10kHz (-3dB)	140Hz to 10kHz (-3dB)
Signal output	Up to 8V peak to peak	Up to 8V peak to peak
Preamp	Single ended, fixed gain	Single ended, fixed gain
Connector type	BNC, 50/75 ohm cable can be used	BNC, 50/75 ohm cable can be used
Elements		
Dimensions	55 x 16 x 10 mm	55 x 16 x 10 mm
Sensitivity	-187dB ref 1V per μ Pa	-187dB ref 1V per μ Pa
Depth recoverable	30m max	30m max
Operating depth	Typical 10m	Typical 10m
Type	Non acceleration cancelling	Non acceleration cancelling
Resonance	@ 9 kHz	@ 9 kHz

Model number	AH365/20	AH610/24LF (Low Frequency)
Tow leader	50m	50m
Array Tube type	Polyurethane	Polyurethane
Array tube length	10m	14
Number of elements	20	24
Element spacing	365mm	610mm
Array sensitivity	-161dB ref 1V per μ Pa	-162dB ref 1V per μ Pa
Fluid type	Polydimethylsiloxane, PMX561	Polydimethylsiloxane, PMX561
Power	Battery, 9V alkaline, PP3/MN1604	24Vdc
Frequency response	140Hz to 10kHz (-3dB)	115Hz to 7.2kHz (-3dB)
Signal output	Up to 8V peak to peak	Up to 8V peak to peak
Preamp	Single ended, fixed gain	Differential output, link adjustable gain
Connector type	BNC, 50/75 ohm cable can be used	BNC, 50/75 ohm cable can be used
Elements		
Dimensions	55 x 16 x 10 mm	53 x 20mm
Sensitivity	-187dB ref 1V per μ Pa	-192dB ref 1V per μ Pa
Depth recoverable	30m max	30m max
Operating depth	Typical 10m	Typical 10m
Type	Non acceleration cancelling	Acceleration cancelling
Resonance	@ 9 kHz	@ 9 kHz

Other element configurations are available to order



Due to continual product improvement, specification information may be subject to change without notice.
Streamer Hydrophones/July 2016
©Applied Acoustic Engineering Ltd.



Applied Acoustic Engineering Ltd
Marine House, Marine Park
Gapton Hall Road
Great Yarmouth NR31 0NB
United Kingdom

T +44(0)1493 440355
F +44(0)1493 440720
E general@appliedacoustics.com
W www.appliedacoustics.com